



HARDI KENYA LIMITED

Suppliers of Quality Crop Sprayers

Hardi KS120 Wheelbarrow Sprayer



Hardi Kenya's 120 litre Wheelbarrow Sprayer is compact, versatile and powerful. Ideal for spot spraying in greenhouses and for small scale horticulture and coffee farms

Using the same Powder-coated technique used on all Hardi's products, the KS120's frame is corrosion resistant and easy to clean. The large wheels make the wheelbarrow easily manoeuvrable, even in wet conditions.

The KS has a UV resistant polyethylene tank with a large filling aperture and filter and a suction sump, enabling effective drainage of the chemical.

The Comet APS41 diaphragm pump is connected to a 6hp Briggs & Stratton Vanguard petrol engine through Direct Drive gearbox, and has a maximum output of 40l/min at a pressure of 40bar.

Delivery hoses available include both PVC and high quality rubber pipes rated up to 80/200 bar, mounted on hose holders, and fitted with double-ceramic nozzle spray lances or venturi-type spray pistols. The nominal length supplied is 2 x 50m.

HARDI KENYA LIMITED

P O Box 47409
GPO - 00100
Nairobi
Kenya

Phone: +254 (0)20 2384212/14
Fax: +254 (0)20 2384206
Email: admin@hardi.co.ke





HARDI KENYA LIMITED

Suppliers of Quality Crop Sprayers

Hardi KS120 Wheelbarrow Sprayer

Specifications

- Tank :* 120 litre PE Blow-moulded
- Pump:* Comet APS41 3-diaphragm
Flow Rate: 40 litres/minute
Max. Pressure: 40 Bar
- Pressure regulator:*
Comet GCP 3-outlet
- Engine:* Briggs & Stratton Vanguard
Fuel: Petrol 4-stroke
Power Output: 6HP
Engine Speed: 3000rpm
- Hoses:* Rubber
80Bar working pressure
200Bar bursting pressure
- PVC
50Bar working pressure
150Bar bursting pressure
- Lances:* Brass double nozzle
with Albus ceramic hollow cone nozzles
Hydra venturi spray pistol
with single ceramic hollow cone nozzle

HARDI KENYA LIMITED

