

DATASHEET FIELD-IQ CROP INPUT CONTROL SYSTEM



Trimble's Field-IQ™ crop input control system is a flow and application control system that prevents seed and fertiliser overlap, controls the rate of material applications, monitors seed delivery and fertiliser blockage, and controls the height of spray booms. The Field-IQ system runs on the TMX-2050™ display, FmX® integrated display, and CFX-750™ display. Each of these displays supports a different combination of Field-IQ functionality—giving you the ability to choose the interface option that fits your needs.

Field-IQ For Spraying

Overlapping spray inputs increases fertiliser and chemical costs while risking potential harm to the environment. The Field-IQ system applies the correct amount of fertiliser and chemicals to your field while preventing spray overlap.

Benefits

- Decreases input costs
- Eliminates over-spraying

Applying fertilisers and chemicals from the incorrect distance above the crop can increase the risk of damage to crops and the environment. The Field-IQ system automatically adjusts the height of boom sections with sensors that measure the distance between ground cover or plant canopy.

Benefits

- Provides even application of product
- Reduces operator fatigue

Field-IQ for Planting and Seeding

Overlapping inputs will increase your costs and creates nutrient deficiency in soil due to overpopulation of seed. The Field-IQ system controls planter clutches and a variety of air seeder systems by automatically turning sections on/off based on non-farm zones and previously planted areas.

Benefits

- Eliminates over-planting
- Increases yield

Monitoring seed population, eliminating skips and multiples, and maintaining correct seed spacing are critical in producing the maximum yield per hectare. The Field-IQ system helps growers prevent yield loss by monitoring the results of singulation analysis in real-time so that adjustments can be made immediately.

Benefits

- Ensures proper seed spacing
- Prevents lodging and nutrient competition

Plants can have different nutrient needs throughout the growing season based on soil conditions and other environmental factors. The Field-IQ system monitors and simultaneously varies the rate of materials to precisely plant seeds, apply chemicals and broadcast fertilisers.

Benefits

- Creates uniform yield across fields
- Lessens environmental impact

Automatic Section Control

- Manage seed, liquid, and anhydrous using 2.5 cm control on up to 48 individual sections
- Overlap detection shows where you've been and what you've done
- Eliminate seed overlap in your headlands and point rows with Tru Count Meter Mount™ air clutches
- Eliminate fertiliser overlap with Tru Count LiquiBlock™ valves that easily connect to clutch air lines



Seed Monitoring

- Advanced seed monitoring increases the quality of seed placement by delivering singulation details from the seeding system to the operator, allowing for on-the-go planter tuning
- Prevent costly planter problems by catching them early before they cause yield reduction
- See results of singulation analysis including information on population, singulation, skips/multiples, spacing, and quality of spacing



Variable Rate Application Control

- Simultaneously control the application rate of different materials (up to 6 with the FmX display and up to 2 with the CFX-750 display), including granular seed, granular fertiliser, liquid, and anhydrous ammonia in different combinations
- Variable rate control of materials can be achieved with a prescription VRA map or in real time with a GreenSeeker system for more efficient fertiliser utilisation
- Automate mapping and record keeping as inputs are applied
- Adjust your seed population, fertiliser rates, or spray application manually or using a prescription created with Farm Works Software® solutions
- Automatically control spinner speed of spreader application systems to evenly distribute nutrients when using the FmX display



Boom Height Control for Sprayers

- Automatically adjust boom height with ultrasonic sensors that measure the distance between ground or crop canopy, resulting in an even application of material
- Minimise environmental impact and ensure the health of neighbouring crops by eliminating off-target applications of products
- Automatic height sensing reduces operator fatigue by eliminating the need for manual boom switching

Trimble Agriculture Division
10368 Westmoor Drive
Westminster, CO 80021
USA
+1-720-887-6100 Phone
+1-720-887-6101 Fax

Trimble Navigation Limited
Corporate Headquarters
935 Stewart Drive
Sunnyvale, CA 94085
USA
+1-408-481-8000 Phone
+1-408-481-7740 Fax

Trimble Germany GmbH
Am Prime Parc 11
65479 Raunheim
GERMANY
+49-6142-2100-0 Phone
+49-6142-2100-140 Fax



www.trimble.com/agriculture