

Hardi Kenya's 200 and 300 litre Trolley Sprayers are purpose-built to provide versatility and convenience in a range of applications, including greenhouse crops and small scale outdoor horticulture.

Mounted on 3 pneumatic tyres, the front one a Low Ground-force Floatation tyre, the TR Trolley's frame is specially designed for its strength and manoeuvrability. The TR Trolley has a UV resistant polyethylene tank has a large filling aperture and filter. An in-tank suction filter provides the second phase of filtration.

The Comet APS41 diaphragm pump is connected to a 6hp Briggs & Stratton Vanguard petrol engine through Direct Drive gearbox, and has a maximum output of 40l/min at a pressure of 40bar.

Delivery hoses available include both PVC and high quality rubber pipes rated up to 80/200 bar, mounted on hose holders, and fitted with double-ceramic nozzle spray lances or venturi-type spray pistols. The nominal length supplied is 2 x 50m.

Product Numbers: TR200: HKE-880822 TR300: HKE-880823



HARDI KENYA LTD CROP SPRAYING SPECIALISTS

Hardi Kenya Ltd, Ruiru P. O. Box 47409-00100 Nairobi, Kenya Tel: (0)20 2384212/4/6 Fax: (0)20 2384206 Web: www.hardi.co.ke http://www.hardi.co.ke

Specifications

Tank: 0 200 / 300 litre PE Blow-moulded

Pump: 2 Comet APS41 3-diaphragm

Flow Rate: 40 litres/minute

Max. Pressure: 40 Bar

Pressure regulator: 3

Comet GCP 3-outlet

Engine:

Briggs & Stratton Vanguard

Fuel: 9 Petrol 4-stoke

Power Output: 6HP

Engine Speed:3000rpm

Hoses: 6 Rubber

80Bar working pressure

200Bar bursting pressure

PVC

50Bar working pressure 150Bar bursting pressure

Lances: Description Brass double nozzle with Albuz ceramic hollow cone nozzles. Hydra venturi spray pistol with single ceramic hollow cone nozzle.

